



Graffiti removal

Materials supplier: Mendeleev Ltd.

Compositions used: Powder Paint Remover No.281.

Date of operation: September, 2011.

Air temperature: +5 to +12°C.

Relative air humidity: 84 to 98%.

Today graffiti is a sort of street art, one of the most popular forms of artistic self-expression all over the world. Graffiti include all kinds of wall drawings – simple words as well as exquisite graphics. от простых слов до изысканных рисунков. Unfortunately, nearly each wall, architecture monument, railroad car or subway station is covered with graffiti. This is but a brief list of what was vandalized with the help of a spray can. Our construction companies, communal services and restoration workers have to paint these drawings over. In Pic.1 it is seen that the painted surface was covered with graffiti and then it was painted over, although the tags should have been washed off first. As graffiti was not removed they emerged through paint coating again. The right solution would be to wash the vandal drawing off the surface. Mendeleev Ltd. experts made their practicable contribution to the struggle against graffiti, having designed Old Paint Remover No.281, a graffiti removal agent.

Pic.1 – Graffiti on a building facade.

Old Paint Remover No.281 is designed to remove thin hard-to-destruct paint coatings following a spraying method.

Pic.2 – Old Paint Remover No.281 with a defiled surface on the background.

Apply Old Paint Remover No.281 with a hand sprayer (it may as well be done with a brush or a roller) and wait for several minutes. The agent does not contain neither acids nor alkalis.

Pic.3 – Apply the agent to remove graffiti layer from the painted surface.

To remove graffiti spray Old Paint Remover No.281 evenly onto the drawing. Product consumption in this case will be minimum 200 ml per square meter.

Pic.4 – Clean the surface applying Old Paint Remover No.281 onto the graffiti with a hand sprayer.

Wear overalls and rubber gloves and safety when working with the product.

Pic.5 – Old Paint Remover No.281 exposure.

Exposure time is 2 to 10 minutes. Graffiti layers gradually disappear.

Pic.6 – One-time surface treatment against graffiti.

To enhance wall surface cleaning, increase Old Paint Remover No.281 consumption and exposure time.

Pic.7 – Apply Old Paint Remover No.281 with a brush.

To clean the most defiled surface rub Old Paint Remover No.281 into it with a brush or a rag.

Pic.8 – Rinse the surface with water using a hand sprayer.

Flush the disrupted paint with a radial water jet (using Kärcher-type high-pressure cleaners).

Pic.9 – Rinse the surface with water using a hand sprayer.

The wall cleaned from graffiti with Old Paint Remover No.281

Pic.10 – Building facade surface, coated with facade paint after all graffiti had been removed.



ООО «Менделеев»

Разработка и производство реставрационных и лакокрасочных материалов

Адрес: 191040, Санкт-Петербург, Лиговский проспект, д. 50 корп. 17, вход №2, домофон «1»

Телефоны: (812) 327-44-24, 327-44-25, 327-44-27

Е-mail: mendelev@dmendelev.com

Часы работы: пн-пт 10:00-18:00, обед 14:00-15:00

Сайт: www.dmendelev.com

A cleaning company refreshed the building facade. Please note that not a single trace of graffiti was left. They all had been removed with Old Paint Remover No.281 beforehand.

- anti-graffiti
- graphic element
- graffiti
- paint inscriptions on facades
- drawings on walls
- tags
- hand sprayer
- adhesive layer removal
- graffiti removal